



LED Explosion Proof Street Lights

Data

Power	ENEP-40W-18	ENEP-50W-18	ENEP-60W-18	ENEP-70W-18	ENEP-80W-18	ENEP-100W-18	ENEP-120W-18	ENEP-150W-18	ENEP-200W-18	ENEP-240W-18
Input Voltage	100-277VAC Ex db eb IB T6 Gb WF2									
Lamp Shade	Grey/Yellow									
Lumen (Lm)	4240	5300	6360	7420	8480	10600	12720	15900	21200	25440
Color	3000K/4000K/5000K/5700K									
LED	CREE									
Beam Angle	60°/90°/120°									
PF	0.95									
CRI	70									
IP Rating	IP66									



Dimensions & Packings

Power	Dimension (mm)			Packing				
	L	W	H	L (mm)	W (mm)	H (mm)	GW(kg)	Quantity
40W	468	190	62	49	21	9	4.4	1
50W	468	190	62	49	21	9	4.4	1
60W	468	190	62	49	21	9	4.4	1
70W	545	244	70	56	25.5	9	6.5	1
80W	545	244	70	56	25.5	9	6.5	1
100W	545	244	70	56	25.5	9	6.5	1
120W	595	244	70	60.5	25.5	9	7.7	1
150W	595	244	70	60.5	25.5	9	7.7	1
200W	655	280	70	67	29.5	9	9.8	1
240W	655	280	70	67	29.5	9	9.8	1

