

ENELTEC[®]

brighten your ideas

Portable COB LED Flood Lights



EPISTAR



Specification:

- Nicely treated die-casting ADC12 aluminum alloy housing
- 4mm tempered glass cover, strong protection and good optical function
- Waterproof: IP65
- Operating Temperature: -20-50°C
- Storage Temperature: -40-60°C

Application:

Play Ground, Construction Building, Garden or Park



www.eneltec-led.com



Lamp Body

Using intergrated casting aluminum materials. crush resistance, fashionable & good gloss.

Top Facing

High strength tempered glass lens
Uniform light, high light transmittance;
Cover the Spray paint grinding technology, elegant appearance, not rust.

Radiator

The integration die-casting radiator. Strong convection design is better to heat dissipation, Effective guarantee the lamp bead life.



Fittings

H base fixed can be placed in any emergency auxiliary lighting, Match travel charger and car charger, More convenient.



Secured large screws



Strong convection radiator



Integrative radiator



"H" holder



Waterproof rubber plug

Waterproof design care every detail, waterproof grade IP65, better application in a harsh environment,

Car charger



Travel charger

Travel charger volume is relatively small easy to carry.

● Parts List

1. Holder
2. Fixing screw
3. Swivelling mounting bracket (u-shaped)
4. Stand
5. Locking screw for stand
6. On/Off switch
7. Charging socket



● Data

Model No.	ENFL-10W-01POR	ENFL-20W-01POR	ENFL-30W-01POR	ENFL-50W-01POR
Power (W)	10	20	30	50
Lumen (lm)	1000	2000	3000	5000
CRI	>80			
Beam Angle	120°			
Color	2700-3200K / 4000-4500K / 6000-6500K			
IP Grade	IP65			
LED	EPISTAR 35mil×1PC			
LED Driver	CE Driver			
Battery	2200MAH Rechargeable Battery 4 hours working	4400MAH Rechargeable Battery 4 hours working	6600MAH Rechargeable Battery 4 hours working	8800MAH Rechargeable Battery 4 hours working
Product Dimension (mm)	195×190×150	245×220×205	260×260×280	330×330×205
Packing Dimension (mm)	8PCS 370×370×360	6PCS 550×480×250	4PCS 545×480×325	4PCS 845×345×350
Net Weight/ Gross Weight (Kg)	8PCS 8.6/9.5	6PCS 10.0/11.0	4PCS 12.0/13.2	4PCS 14.5/16.0